

## PSSu BP 1/8 C-J

312603



PSSu, base module for electronic modules, periphery, 1-row, 4 connection levels, 8 terminals, spring-loaded connection, cold junction compensation with integral Pt1000.

## Technical details

### General data

Approval: CE, UKCA,

Application range: Standard/failsafe

### Technical data

### Environmental data

Humidity rating: 93 % r. h. at 40 °C

Condensation permitted?: Not permitted

Vibration to standard ...: EN 60068-2-6

Acc. shock to standard1: 15g

### Mechanical data

Housing material lower section: PA

Housing material upper part: PC

Connection terminal: Cage clamp terminal

Terminal style: fixed

Height dimension: 129 mm

Width dimension: 12.6 mm

Net weight: 37 g


Gross weight: 49 g

### Environment

RoHS directive: 2011/65/EU, 2015/863/EU


RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
<b>Commercial data</b>	
Harmonized System Code:	85369095
UNSPSC 25:	39122331
EAN-Code:	4046548056754
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27242603
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC001598
Volume:	0 dm3

## Optional accessories



312960

PSSu A LA2 ( 10x50 pcs.)




312962

PSSu A LA4 (10x50 pcs.)



312951

PSSu A ME1 (10x6 pcs.)



312961

PSSu A LA3 (10x50 pcs.)

	312950	PSSu A ME0 (10x6 pcs.)
	312953	PSSu A ME3 (10x6 pcs.)
	312952	PSSu A ME2 (10x6 pcs.)
	312963	PSSu A SH S (10 pcs.)
	312955	PSSu A ME5 (10x6 pcs.)
	312900	PSSu A ET (10 pcs.)
	312954	PSSu A ME4 (10x6 pcs.)
	312957	PSSu A ME7 (10x6 pcs.)
	312902	PSSu A EC



312956

PSSu A ME5 (10x6 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



312901

PSSu A ETM (2 pcs.)



312959

PSSu A LA1 (10x50 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312949

PSSu A ET PE (10 pcs.)