

PSSu XB F -T

314092



PSSu, base station, failsafe and standard, expansion module for cable-based module bus extension for FS and ST data and the module supply, for increased environmental requirements.

Technical details

General data	
Approval:	CE, UKCA, cULus Listed, KOSHA, TÜV, EAC (Eurasian)
Application range:	Standard/failsafe
Technical data	
Environmental data	
Climatic suitability to ...:	EN 60068-2-30, EN 60068-2-2, EN 60068-2-1, EN 60068-2-78, EN 60068-2-14
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	-40 - 70 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Condensation permitted?:	Briefly
Perm. operating height ASL:	5000 m
EMC to standard ...:	EN 61131-2, EN 61000-6-2, EN 61000-6-4
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	150 m/s ²
Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	II
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529

Mechanical data	
Housing material lower section:	PC
Housing material front plate:	PC
Housing material code:	PA
Terminal style:	plug-in
Height dimension:	76 mm
Width dimension:	25.2 mm
Depth dimension:	60.2 mm
Net weight:	35 g
Gross weight:	45 g
Name of coding element:	L
Colour of coding element:	Yellow
Environment	
REACH compliance:	contains min. 1 SVHC-substance
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85389091
UNSPSC 25:	39122331
EAN-Code:	4046548054279
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27242205
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC001422
Volume:	0.146 dm ³

Obligatory accessories

	312631	PSSu BP-C 2/16 C
	314628	PSSu BP 2/16 S-T
	314629	PSSu BP 2/16 C-T
	314093	PSSu XR F -T
	312629	PSSu BP 2/16 C
	312628	PSSu BP 2/16 S
	314631	PSSu BP-C 2/8 C-T
	312630	PSSu BP-C 2/16 S
	314630	PSSu BP-C 2/8 S-T